

# High-speed Impact Dot Printer

# CD-S500/501/503

## Features

- High-speed printing :  
Approx.5.0 lines/sec.
- Paper-drop-in style
- Logic-seeking control
- Optional interface cards
- Selectable paper width
- Two color printing
- Page mode printing
- ESC/POS compatibility
- 3 PLY printing capability
- Built-in buzzer
- Built-in NV Memory  
(Logo registration)
- Black-mark sensor (Option)
- Memory switch function
- High reliability and durability

## Applications

- Receipt
- Coupon
- Ticket
- Daily report
- Kitchen
- Delivery slip

## Model name

- CD-S500 :  
Standard model (without auto cutter)
- CD-S501 :  
With auto cutter model
- CD-S503 :  
With auto cutter and auto winder model

## Specifications

Printing method	Serial dot impact (Logic-seeking control)
Printing direction	Bi-directional
Font	7x9 or 9x9 matrix
Number of columns	40/42 columns or 33/35 columns (76.2mm paper width) 36/30 columns or 38/31 columns (69.5mm paper width) 30/25 columns or 31/26 columns (57.5mm paper width)
Printing width	76.2/69.5/57.5±0.5mm paper
Printing speed	5.0 lines/sec.at 76.2mm width+40 columns 5.4 lines/sec.at 69.5mm width+36 columns 6.0 lines/sec.at 57.5mm width+30 columns
Character size (WxH)	1.25x3.12mm(7x9 dots), 1.57x3.12mm(9x9 dots)
Character set	Alphanumeric, International, Code page 437,850,860,863,865, 852,866,857,858, WPC1252
Line spacing	1/144 inch(min)
Line feed speed	40 lines/sec.
Paper feed method	Friction
Paper	76.2/69.5/57.5±0.5mmx ϕ 83mm Thickness:0.06-0.085mm(1 Ply) 1Ply/2Ply/3Ply copy paper 0.05 - 0.14mm(Copy paper cut) 0.05 - 0.20mm(Copy paper print)
Interface	Parallel:IEEE1284 and Centronics compliant or Serial:RS-232C or USB
Input buffer	4K/40 bytes
NV bit map data area	128K bytes
Drawer kick-out	2 drawers
Ink ribbon	Red/Black, Black, Purple, Cassette
Power supply	DC24V±7%
AC adapter	Input:AC 100-230V,1.3A Output:DC24V±5%
Weight	Approx.2.8kg(standard type) 3.2kg(With winder type)
Dimensions (WxDxH)	156x247.7x174.4mm(standard type) 156x247.7x132mm(Ext AC adapter) 156x277.7x197.8mm(With winder type) 156x277.7x157mm(Ext AC adapter)
Operating environment	0 - 50°C, 10 - 90% RH
Storage environment	-20 - 70°C, 5 - 90% RH
Reliability	Printer:MCCBF 7.5 million lines Print Head:150 million characters Cutter:1,000,000 cuts
Safety standard	CE marking Class A, FCC Class A, UL1950, VCCI Class A



Wall mount kit (option)



Model: CD-S500S  
Standard Model



Model: CD-S500S  
Vertical solution  
in black



Model: CD-S503S  
With auto cutter/  
winder Model

## CITIZEN GROUP Japan CBM Corporation

Information Systems Division  
5-68-10 Nakano, Nakano-ku, Tokyo, 164-0001 Japan  
Tel: (81)-3-5345-7540 Fax: (81)-3-5345-7541  
E-mail: info-sys@jcbm.co.jp http://www.jcbm.co.jp  
CITIZEN IS A REGISTERED TRADEMARK OF CITIZEN WATCH CO., LTD., JAPAN  
All specifications are subject to change without prior notice.  
All trademarks or registered trademarks are the property of their respective owners.