

**EPSON**  
EXCEED YOUR VISION

# TM-T88IV THERMAL PRINTER

POS  
PRINTER



## Latest Generation of Industry Leading TM-T88 Series

- Fully compatible with TM-T88III
- High speed printing - up to 200mm / sec
- High speed graphic processing, including 2 colour thermal capability
- Integration smarts, including automatic-status-back and maintenance memory
- Intuitive case design, including improved spill resistance



# EPSON TM-T88IV Specifications



1.8Kg

EPSON AUSTRALIA  
CUSTOMER SERVICE LINE  
**Tel: 1300 304 POS**

VISIT OUR WEBSITE:  
**www.epson.com.au**

HEAD OFFICE  
SYDNEY  
3 Talavera Road  
North Ryde, NSW 2113  
Tel: (02) 8899 3666

EPSON NEW ZEALAND  
CUSTOMER SERVICE LINE  
**Tel: 0800 443 478**

ABN 91 002 625 783  
02/06

## The Epson TM-T88IV – POS Printer

The Epson TM-T88IV is the high-speed thermal receipt printer with compact design and improved printing performance, the powerful successor to the Epson TM-T88III. Built with all the advantages of the Epson TM-T88III, the Epson TM-T88IV provides faster printing with the same high reliability, ideal for high-volume transaction point environments.

### Fully Compatible with the Epson TM-T88III

The Epson TM-T88IV has all the benefits of the Epson TM-T88III with improved performance.

### Fast and Versatile Printing

The Epson TM-T88IV prints receipts at speeds of up to 200 mm per second for both text and graphics - 25% faster than the Epson TM-T88III. With two-colour\*, advanced graphic and barcode (PDF417 and QR code) printing capability, this printer provides highly customised receipts including logos and promotional messages. Its flexible page mode gives you a choice of receipt layouts.

\*Max. two-colour printing speed is 100 mm/sec.

\*To print in two colours, users must load dedicated thermal paper and set the printer to the two-colour printing mode.

### Easy Operation

Drop-in paper loading and standard autocutter provide easy user operation.



### High Reliability

With an MCBF of 52 million lines of receipt printing, the Epson TM-T88IV delivers outstanding reliability that is rugged enough for high-volume environments.

### Compact Design

The Epson TM-T88IV has a small footprint that allows for flexible placement on your counter or wall (using an optional wall-hanging bracket), freeing up valuable counter space. Furthermore, the Epson TM-T88IV offers an improved paper cover design for increased spill resistance. Two case colours (Epson Cool White or Epson Dark Grey) are available to suit your needs.

<b>PRINT METHOD</b>	Thermal line printing
<b>PRINT FONT</b>	
FONT	9 X 17 / 12 x 24
COLUMN CAPACITY	56 / 42 columns
CHARACTER SIZE	0.99mm(W) x 2.4mm(H) 1.41mm(W) x 3.39mm(H)
CHARACTER SET	95 Alphanumeric, 37 International, 128 x 11 Graphic Traditional / Simplified Chinese, Japanese, Korean
<b>BAR CODE</b>	
	UPC-A, UPC-E, JAN8 (EAN), JAN13 (EAN), CODE39, CODE93, CODE128, ITF, CODABAR Two-dimensional code: PDF417, QRCode
<b>CHARACTERS PER INCH</b>	20.0 cpi / 15.0 cpi
<b>INTERFACES</b>	
	RS-232, Bi-directional parallel Dealer option: RS-486, USB, 10 Base-T I/F
<b>DATA BUFFER</b>	4 KB or 45 bytes
<b>PRINT SPEED</b>	Max. 200mm / sec

<b>PAPER DIMENSIONS</b>	79.5mm ± 0.5mm(W) x dia. 83.0mm
<b>THICKNESS</b>	0.06mm to 0.07mm
<b>POWER</b>	24VDC ± 7%
<b>POWER CONSUMPTION</b>	Approx 1.8A (mean)
<b>D.K.D. FUNCTION</b>	2 drivers
<b>RELIABILITY</b>	
	MTBF: 360,000 hours MCBF: 52,000,000 lines
<b>OVERALL DIMENSIONS</b>	145mm(W) x 195mm(D) x 148mm(H)
<b>MASS (APPROX.)</b>	1.8kg
<b>EMC STANDARDS</b>	
	FCC, VCCI class A CE marking, AS / NZS CISPR22 class B
<b>POWER SUPPLY (OPTION)</b>	PS-180
<b>OPTION</b>	Wall-hanging bracket WH-10
<b>SAFETY STANDARDS</b>	UL / CSA / EN